

Riblet Development Company, Inc.

A MEMBER OF THE RIBLET GROUP
P.O. BOX 3523 SPOKANE, WASHINGTON 99220-3523 U.S.A.

PHONE 509 483-8555
FAX 509 483-1996

Estimate No. 1848 E.O. No. 13010 Date: November 14, 1996 By: DS

A. Specifications for Vista Ridge Quad

1. Horizontal Length: 1893 ft. 577 m.
2. Vertical Rise: 403 ft. 123 m.
- Slope Length: 1961 ft. 598 m.
3. Survey Furnished By: Owner
4. Rotation of Lift in Plan View: CCW
5. Snow Depth, Ft.:

| <u>Lower Term.</u> | <u>Along Line</u> | <u>Upper Term.</u> | <u>Ski Under?</u> |
|--------------------|-------------------|--------------------|-------------------|
| TBS | TBS | TBS | Yes |
6. Capacity: **2400** pph. Maximum 1 chair in 10 loaded downhill.
7. Speed: **450** ft./min. 2.29 m./sec.
8. Chair Spacing: 45 ft. 13.72 m.
- Chair Interval: 6.00 sec.
9. Chairs: 88 Quad bail with damper, restraint bar, thick pad, sign mount.
10. Towers: 12 Pylon with work platforms and lifting beams.
11. Lower Terminal: Fixed Idler, Bullwheel Loading.
12. Upper Terminal: Overhead tension drive, bullwheel unloading.
13. Prime Mover: 150 HP DC-SCR drive, variable speed.
14. Auxiliary Prime Mover: Used Gasoline Engine, Unloading Duty Only.
15. Traction Rope: 1-3/8" Dia., 6 x 25 IPS
- Line Gauge: 13.5 Ft.

Special Features (supersedes any language in spec. pages 2 thru 7).
Detensioner included for installing / relocating chair clips.
Work chair included.
Wire tray for drive terminal included.
See alternates for reduced initial capacity.